

SCS	IT	SCS	IT
	PROCUREMENT SERVICES		PROCUREMENT SERVICES
SCS	IT	Tel.: +41 61 927 92 92 verkauf@scsit.ch	
	PROCUREMENT SERVICES		

be quiet! Netzteil Dark Power 13 1000 W, Kühlungstyp: Lüfter



✓ Delivery time: 2- 4 days

CHF **251.02**

CHF **271.35** incl.

be quiet! Netzteil Dark Power 13 1000 W, Kühlungstyp: Lüfter, 80 PLUS Zertifikat: 80 PLUS Platinum, Netzteil Nennleistung: 1000 W, Netzteil Kabelstrang: Voll-modular, Netzteil Formfaktor: ATX

Manufacturer be quiet!
EAN 4260052189405
Manufacturer# BN335
Energy label



Description

The Dark Power 13 1000 Watt offers 80 PLUS Titanium efficiency, virtually inaudible operation and ATX 3.0 compatibility for full compatibility with next-generation GPUs.

Specification

Product	be quiet! Dark Power 13 - power supply - 1000 Watt
Description	
Device Type	Power supply - active Power Factor Correction (PFC) - internal
Specification	ATX12V 3.0/ EPS12V 2.92
Compliance	
80 PLUS	80 PLUS Titanium
Certification	

Weight	2.03 kg
Input Voltage	AC 100-240 V
Output Voltage	+3.3, +5, ±12 V
Power Capacity	1000 Watt
Output Current	+3.3V - 25 A +5V - 25 A +12V1 - 32 A +12V2 - 32 A +12V3 - 40 A +12V4 - 40 A -12V - 0.5 A +5VSB - 3 A
Output connectors	1 x power 24 pin ATX with detachable 4 pin section 1 x power 4+4 pin 1 x power P8 1 x 12VHPWR 4 x 8 pin PCI Express power with detachable 2 pin section 13 x 15 pin Serial ATA power 3 x Parallel ATA
Modular Cable Management	Yes
Cooling System	135 mm fan
Included Accessories	Screws, cable ties, thumbscrews, overclock slot bracket with switch, overclock jumper
Colour	Black
Dimensions (WxDxH)	15 cm x 17.5 cm x 8.6 cm
Environmental Standards	ENERGY STAR
Manufacturer Warranty	10 years warranty

Techn. Details

Device Type	Power supply - active Power Factor Correction (PFC) - internal
Specification Compliance	ATX12V 3.0/ EPS12V 2.92
PSU Form Factor	ATX
Colour	Black
Input Voltage	AC 100-240 V
Frequency Required	50 - 60 Hz

Power Output Connectors Details	1 x power 24 pin ATX with detachable 4 pin section 1 x power 4+4 pin 1 x power P8 1 x 12VHPWR 4 x 8 pin PCI Express power with detachable 2 pin section 13 x 15 pin Serial ATA power 3 x Parallel ATA
Output Voltage	+3.3, +5, ±12 V
Power Capacity	1000 Watt
Output Current	+3.3V - 25 A +5V - 25 A +12V1 - 32 A +12V2 - 32 A +12V3 - 40 A +12V4 - 40 A -12V - 0.5 A +5VSB - 3 A
Efficiency	94.8% at 20% Load (230 VAC), 72% at 2% Load (230 VAC), 90.7% at 10% Load (230 VAC), 95.2% at 50% Load (230 VAC), 93.3% at 100% Load (230VAC)
Power Factor (PF)	0.98
Modular Cable Management	Yes
80 PLUS Certification	80 PLUS Titanium
Included Accessories	Screws, cable ties, thumbscrews, overclock slot bracket with switch, overclock jumper
Cooling System	135 mm fan
Features	Silent Wings, Modern Standby, overheat protection, over current protection, over voltage protection, overpower protection, undervoltage protection, short-circuit protection, DC-DC technology, Full Bridge topology, Synchronous Rectifier (SR) technology, Surge & Inrush Protection (SIP), Active Rectifier, LLC Full Bridge Topology
Compliant Standards	TUV, BSMI, CB, CCC, FCC, RoHS, WEEE, cTUVus, ERP, RCM, cRUus, CU, UKCA, Triman
ENERGY STAR	Yes
Service & Support	Limited warranty - 10 years
Max Operating Temperature	40 °C
Width	15 cm
Depth	17.5 cm

Height	8.6 cm
Weight	2.03 kg
Shipping Width	12 cm
Shipping Depth	35 cm
Shipping Height	27 cm
Shipping Weight	4.48 kg

Date added: 2023-01-25 08:48:26 / SID: 1723484 / DID: 1513185