

|            |                         |                                            |                         |
|------------|-------------------------|--------------------------------------------|-------------------------|
| <b>SCS</b> | <b>IT</b>               | <b>SCS</b>                                 | <b>IT</b>               |
|            | PROCUREMENT<br>SERVICES |                                            | PROCUREMENT<br>SERVICES |
| <b>SCS</b> | <b>IT</b>               | Tel.: +41 61 927 92 92<br>verkauf@scsit.ch |                         |
|            | PROCUREMENT<br>SERVICES |                                            |                         |

## MeanWell Chasisnetzgerät RS-25-12



 Next possible delivery date: May 4, 2024

CHF **18.83**

CHF **20.35** incl.

**MeanWell Chasisnetzgerät RS-25-12 25.2 W, 12 V, Eingangsspannung: 88 - 264 V, Netzteil Nennleistung: 25.2 W, Ausgangsspannung: 12 V, Anschluss PRI: Klemme, Netzteil Art: Chasisnetzgerät, Nennausgangsstrom: 2.1 A, Anschluss SEC: Klemme, Ripple & Noise: max. 120mVp-p, Spannungstoleranz: +-1%, Effizienz: 79%**

|               |               |
|---------------|---------------|
| Manufacturer  | MeanWell      |
| EAN           | 7612946302327 |
| Manufacturer# | RS-25-12      |

### Description

Marketing description is not available.

### Specification

|                       |                                                            |
|-----------------------|------------------------------------------------------------|
| Product Description   | Mean Well RS-25 series RS-25-12 - power supply - 25.2 Watt |
| Device Type           | Power supply - internal                                    |
| Input Voltage         | AC 115/230 V                                               |
| Output Voltage        | 12 V ± 1%                                                  |
| Power Capacity        | 25.2 Watt                                                  |
| Dimensions (WxDxH)    | 5.1 cm x 7.8 cm x 2.8 cm                                   |
| Manufacturer Warranty | 3-year warranty                                            |

Techn. Details

|                           |                                                                                         |
|---------------------------|-----------------------------------------------------------------------------------------|
| Device Type               | Power supply - internal                                                                 |
| Input Voltage             | AC 115/230 V                                                                            |
| Input Voltage Range       | AC 88 - 264 / DC 125 - 373 V                                                            |
| Frequency Required        | 47 - 63 Hz                                                                              |
| Output Voltage            | 12 V ± 1%                                                                               |
| Power Capacity            | 25.2 Watt                                                                               |
| Efficiency                | 81.5%                                                                                   |
| MTBF                      | 244,000 hour(s)                                                                         |
| Features                  | LED indicators, over voltage protection, overload protection, short-circuit protection  |
| Compliant Standards       | TUV, EN 61000-3-2, EN 61000-3-3, EN55022 Class B, UL 60950-1, EN 60950-1, MIL-HDBK-217F |
| Service & Support         | Limited warranty - 3 years                                                              |
| Min Operating Temperature | -20 °C                                                                                  |
| Max Operating Temperature | 70 °C                                                                                   |
| Humidity Range Operating  | 20 - 90% (non-condensing)                                                               |
| Width                     | 5.1 cm                                                                                  |
| Depth                     | 7.8 cm                                                                                  |
| Height                    | 2.8 cm                                                                                  |
| Shipping Weight           | 200 g                                                                                   |