

SCS	IT	SCS	IT
	PROCUREMENT SERVICES		PROCUREMENT SERVICES
SCS	IT	Tel.: +41 61 927 92 92 verkauf@scsit.ch	
	PROCUREMENT SERVICES		

Raritan KVM Switch Dominion KX III 816



 Delivery date unknown

List Price:
Instant Savings:

~~CHF 7,357.95~~
CHF -86.50

CHF **6,726.60**

CHF **7,271.45** incl.

Raritan KVM Switch Dominion KX III 816, Konsolen Ports: USB 2.0, RJ-45, DVI-D, Computer Ports: RJ-45, KVM-Art: Netzwerk, Anzahl Geräte: 16, Montage: 19" Rack, Stromversorgung: Internes Netzteil

Manufacturer	Raritan
Manufacturer#	DKX3-816

Description

Raritan Dominion DKX3-816 video processing engine supports dynamic broadcast applications that require HD resolution, 24-bit color, digital audio, dual monitors and DVI, HDMI, DisplayPort, USB-C and VGA video. View streaming video at 30 fps over your LAN.

Specification

Product Description	Raritan Dominion DKX3-816 - KVM switch - rack-mountable
Device Type	KVM switch - CAT5
Enclosure Type	Rack-mountable 1U
Subtype	KVM
Ports	16 x KVM port(s)
KVM Users Qty	1 local user, 8 IP users

Remote Management Protocol	SNMP 2, SNMP 3, HTTP, HTTPS
Features	Syslog support, IPv6 support, IPv4 support
Power	AC 120/230 V (50/60 Hz) 1.8 A
Power Redundancy	Yes
Dimensions (WxDxH)	44 cm x 33.4 cm x 4.4 cm
Weight	4.52 kg
Manufacturer Warranty	2-year warranty

Techn. Details	
Device Type	KVM switch
Enclosure Type	Rack-mountable 1U
Subtype	KVM
Ports	16 x KVM port(s)
KVM Local Users Qty	1 local user
KVM IP Users Qty	8 IP users
Server Connection Via Twisted Pair	CAT5
Keyboard / Mouse Interface	USB
Remote Management Protocol	SNMP 2, SNMP 3, HTTP, HTTPS
Encryption Algorithm	FIPS 140-2, 128-bit AES, 256-bit AES
Authentication Method	RADIUS, PAP, CHAP, LDAP, Active Directory
Max Resolution	1920 x 1200
Features	Syslog support, IPv6 support, IPv4 support, server connection via twisted pair
Interfaces	16 x KVM RJ-45 1 x modem DB-9 4 x USB Type A 1 x RJ-45 1 x DVI-D 2 x 1000Base-T RJ-45
Power Device	Internal power supply
Installed Qty	2
Max Supported Qty	2
Power Redundancy	Yes

Power Redundancy Scheme	1+1
Voltage Required	AC 120/230 V (50/60 Hz)
Electric Current Required	1.8 A
Power Consumption Operational	60 Watt
Rack Mounting Kit	Included
Width	44 cm
Depth	33.4 cm
Height	4.4 cm
Weight	4.52 kg
Service & Support	Limited warranty - advance parts replacement - 2 years
Min Operating Temperature	0 °C
Max Operating Temperature	45 °C
Humidity Range Operating	0 - 85%

Related Prod.

Patchkabel (9)



Wirewin Slimpatchkabel Cat 6A, U/FTP, 2m, Weiss, Farbe: Weiss, Form: Rund & Dünn, Zusatzfunktionen: Mit Klinkenschutz, Längenaufdruck auf Stecker, Länge: 2 m, Anschlüsse LAN: RJ45 - RJ45, Produkttyp: Slimpatchkabel



CHF **12.58**
CHF **13.60** incl.



Wirewin Slimpatchkabel Cat 6A, U/FTP, 1.5m, Grau, Farbe: Grau, Form: Flach, Zusatzfunktionen: Mit Klinkenschutz, Längenaufdruck auf Stecker, Länge: 1.5 m, Anschlüsse LAN: RJ45 - RJ45, Produkttyp: Slimpatchkabel



CHF **11.56**
CHF **12.50** incl.



Wirewin Slimpatchkabel Cat 6, STP, 1 m, Violett, Farbe: Violett, Form: Flach, Zusatzfunktionen: Mit Klinkenschutz, Längenaufdruck auf Stecker, Länge: 1 m, Anschlüsse LAN: RJ45 - RJ45, Produkttyp: Slimpatchkabel



CHF **10.73**
CHF **11.60** incl.

KVM-Kabel (7)



Raritan KVM-Kabel D2CIM-DVUSB-DVI



CHF **192.46**
CHF **208.05**



Raritan KVM-Kabel D2CIM-VUSB



incl.

CHF **152.08**

CHF **164.40**

incl.



Raritan KVM-Kabel D2CIM-DVUSB-DP



CHF **191.40**

CHF **206.90**

incl.

Date added: 2020-12-23 08:39:58 / SID: 940024 / DID: 1146638