

SCS	IT	SCS	IT
	PROCUREMENT SERVICES		PROCUREMENT SERVICES
SCS	IT	Tel.: +41 61 927 92 92 verkauf@scsit.ch	
	PROCUREMENT SERVICES		

Hewlett-Packard HPE PROLIANT DL360 G10 5118



✓ Delivery time: 2- 4 days

CHF **3,055.00**

CHF **3,302.45** incl.

HPE PROLIANT DL360 G10 5118 5118 12C 2.3GHz / 32GB / P408i 1 x 500W

Manufacturer Hewlett-Packard
 EAN 0190017299334
 Manufacturer# P06454-B21
 Tagged as **Top** **AssemblyOK**
 Energy label



Description

Does your data center need a secure, performance driven dense server that you can confidently deploy for virtualization, database, or high-performance computing? The HPE ProLiant DL360 Gen10 server delivers security, agility and flexibility without compromise.

Specification

Product Description	HPE ProLiant DL360 Gen10 Performance - rack-mountable - Xeon Gold 5118 2.3 GHz - 32 GB - no HDD
Type	Server - rack-mountable
Height (Rack Units)	1U
Localisation	Region: Worldwide
Server Scalability	2-way

Processor	1 x Intel Xeon Gold 5118 / 2.3 GHz (, up to 3.2 GHz, (12-core)
Processor Socket	FCLGA3647 Socket
Processor Main Features	Hyper-Threading Technology, Intel Turbo Boost Technology 2
Cache Memory	16.5 MB L3 Cache
Cache Per Processor	16.5 MB
RAM	32 GB (installed) / 1.5 TB (max) - DDR4 SDRAM - Advanced ECC - PC4-21333
Storage Controller	RAID (SATA 6Gb/s / SAS 12Gb/s) - PCIe 3.0 x8 (HPE Smart Array P408i-a); SATA (HPE Smart Array S100i SR Software)
Server Storage Bays	Hot-swap 2.5"
Hard Drive	No HDD
Optical Storage	No optical drive
Card Reader	Yes
Video Memory	16 MB
Networking	1GbE
Power	AC 120/230 V (50/60 Hz)
Power Redundancy	Yes
Software Included	HPE Server UEFI
Dimensions (WxDxH)	43.46 cm x 70.7 cm x 4.29 cm
Weight	13.04 kg
Manufacturer Selling Program	HPE Smart Buy
Environmental Standards	ENERGY STAR Qualified
Manufacturer Warranty	Limited warranty - parts and labour - 3 years - on-site - response time: next business day ; Technical support - software application support - 90 days

Techn. Details

Type	Server
Product Form Factor	Rack-mountable - 1U
Built-in Devices	Led panel, battery
Server Scalability	2-way
Hot-Swap Bays Qty	8
Localisation	Region: Worldwide
CPU	Intel Xeon Gold 5118
Clock Speed	2.3 GHz
Max Turbo Speed	3.2 GHz
Number of Cores	12-core
CPU Qty	1
Max CPU Qty	2
CPU Upgradability	Upgradable
Processor Main Features	Hyper-Threading Technology, Intel Turbo Boost Technology 2
CPU Socket	FCLGA3647 Socket
Chipset Type	Intel C621
Installed Size	L3 Cache - 16.5 MB
Cache Per Processor	16.5 MB
Installed Size	32 GB / 1.5 TB (max)
Technology	DDR4 SDRAM - Advanced ECC
Effective Memory Speed	2400 MHz

Rated Memory Speed	2666 MHz
Memory Specification Compliance	PC4-21333
Form Factor	DIMM 288-pin
Slots	24 (Total) / 23 (empty)
Features	Registered, dual rank, slots 13 - 24 are available in two-processor configuration only
Configuration Features	1 x 32 GB
RAM Supported	3 TB Load-Reduced - ECC 1.5 TB registered - ECC 192 GB Non-Volatile - ECC
Type	No HDD
Type	1 x RAID - PCIe 3.0 x8
Controller Interface Type	SATA 6Gb/s / SAS 12Gb/s
Storage Controller Name	HPE Smart Array P408i-a
Channel Qty	8
RAID Level	RAID 0, RAID 1, RAID 5, RAID 6, RAID 10, RAID 50, RAID 60, RAID 1 ADM, RAID 10 ADM
Buffer Size	2 GB
Type	SATA
Storage Controller Name	HPE Smart Array S100i SR Software
Type	No optical drive
Type	Card reader
Supported Flash Memory Cards	microSD
Monitor Type	None.

Video Memory	16 MB
Video Interfaces	VGA
Interface (Bus) Type	FlexibleLOM
Ethernet Ports	4 x Gigabit Ethernet
Ethernet Controller	HPE 331i
Data Link Protocol	Ethernet, Fast Ethernet, Gigabit Ethernet
Remote Management Protocol	SNMP 3, IPMI 2.0, SMASH CLP
Remote Management Controller	Integrated Lights-Out 5
Features	Wake on LAN (WoL), PXE support
Bays	1 (total) / 1 (free) x external Universal Media Bay ¦ 8 (total) / 8 (free) x hot-swap 2.5" SFF
Slots	1 (total) / 0 (free) x FlexibleLOM - three-quarter-length, full-height (low-profile) ¦ 1 (total) / 1 (free) x PCIe 3.0 x16 - three-quarter-length, full-height ¦ 1 (total) / 0 (free) x PCIe 3.0 x8 - low-profile ¦ 1 (total) / 1 (free) x microSD Card (internal) ¦ 1 (total) / 1 (free) x PCIe x16 - full-height
Interfaces	1 x HPE iLO - Type A (1 in front) ¦ 1 x HPE iLO - RJ-45 (1 rear) ¦ 4 x LAN (Gigabit Ethernet) - RJ-45 (4 rear) ¦ 5 x USB 3.0 (1 front, 2 rear, 2 internal) ¦ 1 x VGA (1 rear)
Included Accessories	HPE Easy Install Rails, HPE standard heatsink, 5 x standard hot plug fans
Cables Included	Power cable
Compliant Standards	AES, FIPS 140-2, IPv6 Ready, PCI DSS, TLS v1.2, ASHRAE Class A4, ASHRAE Class A3, WEEE 2002/95/EC, ACPI 6.1
Manufacturer Selling Program	HPE Smart Buy
Device Type	Power supply - hot-plug
Power Redundancy	Yes

Power Redundancy Scheme	1+1
Installed Qty	2
Max Supported Qty	2
Voltage Required	AC 120/230 V (50/60 Hz)
Power Provided	800 Watt
Software	HPE Server UEFI
ENERGY STAR Certified	Yes
ENERGY STAR Version	2.1
Service & Support	Limited warranty - parts and labour - 3 years - on-site - response time: next business day ! Technical support - software application support - 90 days
Width	43.46 cm
Depth	70.7 cm
Height	4.29 cm
Weight	13.04 kg
Min Operating Temperature	10 °C
Max Operating Temperature	35 °C
Humidity Range Operating	8 - 90% (non-condensing)
Sound Emission	45 dBA

